

# VILLAGE

WALL CERAMIC TILES



Crossville  
Studios

 DECORTILES

# VILLAGE

WALL CERAMIC TILES

VILLAGE OFF WHITE



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE GRIS



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE GLACIAL



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE MARINE



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE HIJAU



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE AGAVE



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE COTTO



10x40 cm | 4"x16"  
BR (GLOSSY)

VILLAGE CARBON



10x40 cm | 4"x16"  
BR (GLOSSY)



WALLS



FIRE PROOF



VOC FREE

# VILLAGE

## WALL CERAMIC TILES



### PRODUCT INFORMATION

Type / Size	Series	Finish	Rectified	Unit	Work Size (mm)	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
Wall Tiles 4"x16"	VILLAGE	Glossy	No	SF	100x400	7 mm	60	14.6	34

### USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior	N/A	✓
Countertops	N/A	
Facades	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

### QUALITY WARRANTY

**QUALITY** Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.

**FIRE PROOF** Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

**VOC FREE** Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

### INSTALLATION AND CARE

Grout Joint Recommendation 2 mm  
 Shade Variation V3 - MODERATE VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less)

### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 20%
Breaking Strength	C648	≥ 125 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4
Frost Resistance	C1026	No
Chemical Resistance	C650	Class A
Stain Resistance	C1378	Class A





