



CRAFT

WALL CERAMIC TILES





CRAFT

CERAMIC WALL TILES

CRAFT SNOW



10x10cm | 4"x4"
BR (GLOSSY)

CRAFT ASH




10x10cm | 4"x4"
BR (GLOSSY)

CRAFT COAL



10x10cm | 4"x4"
BR (GLOSSY)

CRAFT SKY



10x10cm | 4"x4"
BR (GLOSSY)

CRAFT JADE



10x10cm | 4"x4"
BR (GLOSSY)

CRAFT TERRACOTTA



10x10cm | 4"x4"
BR (GLOSSY)



WALLS



FIRE PROOF




VOC FREE



CRAFT

CERAMIC WALL TILES

PRODUCT INFORMATION

Type / Nominal Size	Series	Finish	Rectified	Unit	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
 Wall Tiles 4"x4"	CRAFT	GLOSSY	No	SF	108.9 x 108.9 mm 4 1/4" x 4 1/4"	7.75 mm	80	12.80	100

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior (Residential or Commercial)	N/A	✓
Countertops	N/A	
Facades	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20%
Breaking Strength	C648	120-250 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4-6
Frost Resistance	C1026	No
Chemical Resistance	C650	Resistant

INSTALLATION AND CARE

Grout Joint Recommendation 1/16"
Shade Variation V3

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner for wall tiles cleaning.

QUALITY WARRANTY



Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Recycled Content:
31.5 % Pre-consumer
0 % Post-consumer