

# LAGUNA

PORCELAIN TILES



## LAGUNA PORCELAIN TILES

Laguna White



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Shell



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Beige



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Blue



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Green



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Brown



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Laguna Black



5 x 20 cm | 2" x 8"  
BR ( GLOSSY )

Cover: Laguna Brown  
& Laguna Beige



WALLS



EXTERIOR  
PORCELAIN



FIRE PROOF




VOC FREE

# LAGUNA

## PORCELAIN TILES

### PRODUCT INFORMATION

Product	Finish	Rectified	Unit	Work Size	Thick	Faces	Sq. Ft/ Carton	Pieces/ Carton
 Wall 2"x8"	Glossy	No	SF	2 1/4" x 8"	9 mm	TBI	4.43	36

### USAGE RECOMMENDATION

	Target DOCF Wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors ( Residential or Light Commercial )	≥ 0.42	
Exterior Floor Applications (Including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior ( Residential or Commercial )	N/A	✓
Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	✓

A DCOF value of ≥ 0.42 is the standard for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

### SUSTAINABILITY



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Recycled Content:  
TBI Pre-consumer  
TBI Post-consumer

### INSTALLATION AND CARE

**Grout Joint Recommendation** 1/16"  
**Shade Variation** V3

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane recommends using a cloth with water and a neutral cleaner (soap-less) or a general household cleaner for tiles cleaning.

### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	TBI
DCOF WET	ANSI A137.1 ANSI A326.3	< 0.42
Scratch Hardness	MOHS	TBI
Frost Resistance	C1026	Yes
Chemical Resistance	C650	TBI

### QUALITY CARE



Standard quality tiles manufactured by Eliane Ceramic Tiles meet ISO 13006, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.